

PRIMER-PM82

PRIMER PM82 is a RTV (one or two-component) silicone elastomer primary grip for a wide range of substrates: glass, metals and plastics.

Applications

PRIMER PM82 is particularly suited for the following substrates:

- Polar plastic materials such as polyamide, polycarbonate, ABS....
- Aluminium
- Polished (or not) stainless steel
- Painted, electro-galvanized, bichromated steel

Apply only on dry, clean and perfectly degreased support.

This primer can be applied with a cloth or a brush on surfaces which need to have a good adhesion with cast silicone elastomer. It is also important to wait complete solvent evaporation before pouring the silicone on the treated surface (a white veil must be visible).

Do not accelerate the drying with a heat gun.

Read the safety data sheet carefully to be informed of the risks and precautions related to the use and storage of this product. Do not smoke, eat or drink during application.
Do not handle this product in confined areas without ventilation.

Packaging

PRIMER PM82 is available in metal canister of 250 mL appoved for the transportation of hazardous materials. An application brush is provided into the cap.

REFERENCE	PACKAGING
PM82	250 mL



Physicals and chemicals characteristics

Aspect: Colorless liquid

Density: 0.82

Flash point: 27°C

Drying time: mini 15 min - max 6 hours

VOC (%): 5

Storage, handling and hygiene

PRIMER PM82 is guaranteed for 12 months from the delivery date if stored in its closed original packaging, sheltered from weather and heat sources.

Keep this product away from flames or ignition source (spark) in cool and well ventilated areas.

Avoid exposure to direct sunlight.

Homogenize before use.

Information contained herein is provided in good faith and based on our present knowledge. It is therefore only indications and not of formal constraints, especially if the product is not used in accordance with the applications contained in this data sheet. A pre-test will always be the basis of relevant conclusions for the user.

On the other hand the user of this product agrees to comply with the legislation in force on waste disposal.

Custom's code

PRIMER PM82

38249996